

# OUTLET BOX

▶▶ 696 SERIES

OxBox™

## SPECIFICATION

Sioux Chief 696 Series OxBox single-hole outlet box shall be used where necessary in accessible plumbing applications. Box shall provide an appropriately sized hole for accessible line/fixture. Box shall incorporate mounting tabs, and channel for use with common, galvanized, flat brackets.

## MATERIALS

ABS (white)

## WORKING TEMPERATURE

Melting point: 200°F

Working temperature: 150°F


## DIMENSIONS

<b>A:</b> Rough-in box inner width	4"				
<b>B:</b> Rough-in box overall depth	3½"				
<b>C:</b> Rough-in box inner height	5½"				
<b>D:</b> hole diameter	<b>696-1</b>	<b>696-4</b>	<b>696-5</b>	<b>696-6</b>	<b>696-7</b>
	0.85"	1.04"	1.3125"	1.915"	2.390"

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



696-4



## Create Item Number

### 696-A

e.g. **696-4**: Outlet box with 1.04" diameter hole

#### HOLE SIZE A

- |  |   |
|--|---|
| <b>1</b> = 0.85" hole                    | <b>4</b> = 1.04" hole                     |
| <b>5</b> = 1.3125" hole                  | <b>6</b> = 1.915" hole (1½" Sch. 40 pipe) |
| <b>7</b> = 2.390" hole (2" Sch. 40 pipe) |   |

#### Accessories - Available Separately:

- 696-EX: Frame extension
- 696-1F: Frame only
- 696-LC: Louvered cover
- 696-SC: Solid cover
- 696-BC: Box clip
- 696-CF: Secondary drainage funnel
- 520-09: Support bracket